(19) World Intellectual Property Organization

International Bureau





(43) International Publication Date 22 January 2004 (22.01.2004)

PCT

(10) International Publication Number WO 2004/007054 A1

(51) International Patent Classification7: 25/24

B01D 46/52.

(21) International Application Number:

PCT/US2003/002799

(22) International Filing Date: 31 January 2003 (31.01.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 60/395,009

10 July 2002 (10.07.2002)

- (71) Applicant (for all designated States except US): DON-ALDSON COMPANY, INC. [US/US]; 1400 West 94th Street, P.O. Box 1299, Minneapolis, MN 55440-1299 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): GOLDEN, Patrick [US/US]; 199 West County Road C2, Roseville, MN 55113. (US). REICHTER, Gregory, L. [US/US]; 10617 Hopkins Road, Bloomington, MN 55420 (US). RISCH, Daniel, T.

[US/US]; 1116 136th Street West, Burnsville, MN 55337 (US).


- (74) Agent: BRUESS, Steven, C.; Merchant & Gould P.C., P.O. Box 2903, Minneapolis, MN 55402-0903 (US).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

[Continued on next page]

(54) Title: FLUTED FILTER MEDIUM AND PROCESS FOR ITS MANUFACTURE



(57) Abstract: A fluted filter medium (74) comprising a corrugated filter sheet, where each flute (120) has an end closure defined by a regular fold arrangement in the corresponding corrugation. Each regular fold arrangement has at least four folds. A process for manufacturing the fluted filter medium comprising deforming a portion of each corrugation to define at least one foldable tip, and folding the said tip in order to close the corrugation.